

### Exercise 8.17.

In each case below, describe the language generated by the unrestricted grammar with the given productions. The symbols  $a$ ,  $b$ , and  $c$  are terminals, and all other symbols are variables.

a.

$$S \rightarrow ABCS \mid ABC$$

$$AB \rightarrow BA \quad AC \rightarrow CA \quad BC \rightarrow CB$$

$$BA \rightarrow AB \quad CA \rightarrow AC \quad CB \rightarrow BC$$

$$A \rightarrow a \quad B \rightarrow b \quad C \rightarrow c$$

## Exercise 8.17.

In each case below, describe the language generated by the unrestricted grammar with the given productions. The symbols  $a$ ,  $b$ , and  $c$  are terminals, and all other symbols are variables.

**b.**

$$S \rightarrow LaR \quad L \rightarrow LD \mid LT \mid \Lambda \quad Da \rightarrow aaD \quad Ta \rightarrow aaaT$$

$$DR \rightarrow R \quad TR \rightarrow R \quad R \rightarrow \Lambda$$

### Exercise 8.17.

In each case below, describe the language generated by the unrestricted grammar with the given productions. The symbols  $a$ ,  $b$ , and  $c$  are terminals, and all other symbols are variables.

**c.**

$$S \rightarrow LaMR \quad L \rightarrow LT \mid E$$

$$Ta \rightarrow aT \quad TM \rightarrow aaMT \quad TR \rightarrow aMR$$

$$Ea \rightarrow aE \quad EM \rightarrow E \quad ER \rightarrow \Lambda$$

### Exercise 8.18.

Consider the unrestricted grammar with the following productions.

$$S \rightarrow TD_1D_2 \quad T \rightarrow ABCT \mid \Lambda$$

$$AB \rightarrow BA \quad BA \rightarrow AB \quad CA \rightarrow AC \quad CB \rightarrow BC$$

$$CD_1 \rightarrow D_1C \quad CD_2 \rightarrow D_2a \quad BD_1 \rightarrow D_1b$$

$$A \rightarrow a \quad D_1 \rightarrow \Lambda \quad D_2 \rightarrow \Lambda$$

- a. Describe the language generated by this grammar.
- b. Find a single production that could be substituted for  $BD_1 \rightarrow D_1b$  so that the resulting language would be

$$\{xa^n \mid n \geq 0, |x| = 2n, \text{ and } n_a(x) = n_b(x) = n\}$$

### Exercise 8.19.

For each of the following languages, find an unrestricted grammar that generates the language.

a.  $\{a^n b^n a^n b^n \mid n \geq 0\}$

### Exercise 8.19.

For each of the following languages, find an unrestricted grammar that generates the language.

**c.**  $\{sss \mid s \in \{a, b\}^*\}$

**d.**  $\{ss^r s \mid s \in \{a, b\}^*\}$

## Exercise 8.20.

For each of the following languages, find an unrestricted grammar that generates the language.

a.  $\{x \in \{a, b, c\}^* \mid n_a(x) < n_b(x) \text{ and } n_a(x) < n_c(x)\}$

c.  $\{a^n \mid n = j(j + 1)/2 \text{ for some } j \geq 1\}$

(Suggestion: if a string has  $j$  groups of  $a$ 's, the  $i$ th group containing  $i$   $a$ 's, then you can create  $j + 1$  groups by adding an  $a$  to each of the  $j$  groups and adding a single extra  $a$  at the beginning.)

### Exercise 8.21.

Suppose  $G$  is an unrestricted grammar with start symbol  $T$  that generate the language  $L \subseteq \{a, b\}^*$ . In each part below, another unrestricted grammar is described. Say (in terms of  $L$ ) what language it generates.

**a.** The grammar containing all the variables and all the productions of  $G$ , two additional variables  $S$  (the start variable) and  $E$ , and the additional productions

$$S \rightarrow ET \quad E \rightarrow \Lambda \quad Ea \rightarrow E \quad Eb \rightarrow E$$



### Exercise 8.21.


Suppose  $G$  is an unrestricted grammar with start symbol  $T$  that generate the language  $L \subseteq \{a, b\}^*$ . In each part below, another unrestricted grammar is described. Say (in terms of  $L$ ) what language it generates.

**b.** The grammar containing all the variables and all the productions of  $G$ , four additional variables  $S$  (the start variable),  $F$ ,  $R$ , and  $E$ , and the additional productions

$$\begin{aligned} S &\rightarrow FTR & Fa &\rightarrow aF & Fb &\rightarrow bF & F &\rightarrow E \\ E a &\rightarrow E & E b &\rightarrow E & ER &\rightarrow \Lambda \end{aligned}$$

## Exercise.

For the Turing machine below, give all productions of the second type (to simulate the computation of the Turing machine) that result from the construction in the proof of Theorem 8.14.



### Exercise 8.22.

Figure 7.6 shows the transition diagram for a TM accepting  $XX = \{xx \mid x \in \{a,b\}^*\}$ .

In the grammar obtained from this TM as in the proof of Theorem 8.14, give a derivation for the string  $abab$ .

### **Exercise 8.27.**

Show that if  $L$  is any recursively enumerable language, then  $L$  can be generated by a grammar in which the left side of every production is a string of one or more variables.